



Globe Power's GPFL200 Smart Floodlight uses the latest renewable technology to provide a cost-effective lighting solution that does not require diesel input.

This unit runs for a minimum of 24 hours and can be used across multiple shifts on site, comfortably power an event, or provide a dusk to dawn lighting solution for safety requirements.

- 7 day timer
- AC charger
- Level alarm
- Dusk sensor
- Motion sensor
- Fork pockets
- Lifting lugs
- Tie down points



USER-FRIENDLY OPERATION INTERFACE



SOLAR & LITHIUM IRON PHOSPHATE BATTERY



PORTABLE & EASY TO TRANSPORT



AUSTRALIAN DESIGNED & ENGINEERED

PRODUCT SPECIFICATIONS

GENERAL

Model	GPFL200 - Smart Floodlight v1.6
Lumen Output	23,000
Mast Height	4.6 Metres
Mast Type	Cable winch
Lights	2 x 100w LED Modules (Dimmable)
Coverage	3,700m ² at 5 lux

OPERATIONAL DATA

Wind Rating	100km/h
Working Temperature	0 to 50°C
Light Tilt	0 to 90°
Solar Tilt	0° to 135°
Solar Orientation	0 to 360°
Solar	415Wp

BATTERY

Battery	2.9kWh Lithium LiFePO4
Run Time	24-60 hours
Solar Efficiency	1 hr of sun/3.5 hrs of light

UNIT INFORMATION

Dimensions (Stowed)	1140 x 1000 x 2900 (LxWxH)
Dimensions (Deployed)	1740 x 1240 x 6070 (LxWxH)
Weight	910kg

